



Transmax Offroad 30

Powershift Transmission Fluid

Description

Castrol Transmax Offroad 30 is a transmission lubricant using highly refined mineral oil, designed for use in powershift transmissions, direct drive transmissions, wet disc brakes, final drives and differentials in off road machinery where Caterpillar TO-4 is required. This product is also approved for use where ZF TE-ML 03C and 07F are required and recommended for use in Komatsu off-road machinery drivetrain and hydraulics as well as the now-obsolete Allison C-4 applications.

Advantages

- Excellent oxidation stability maintains high temperature performance and transmission cleanliness during service life.
- Stable friction characteristics eliminate slippage and reduce brake noise.
- Excellent friction performance with a wide range of friction materials ensures smooth positive changes and enhanced friction material durability.
- Improved wear performance extends component life.

Typical Characteristics

Name	Method	Units	Transmax Offroad 30
Density @ 15C, Relative	ASTM D4052	g/ml	0.866
Appearance	Visual	None	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.5
Viscosity, Brookfield @ -25C	ASTM D2983	mPa.s (cP)	39300
Pour Point	ASTM D97	°C	-27
Flash Point, COC	ASTM D92	°C	246

Product Performance Claims

ZF TE-ML 03C, 07F

Meets CAT TO-4

Recommended for use in Komatsu Equipment

Recommended for use where Allison C4 is required

Additional Information

Transmax Offroad 30 is registered under the following ZF approval numbers: ZF000267, ZF000299, ZF004897, ZF005985, ZF006019, ZF006071, ZF 006077, ZF006079

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax Offroad 30

02 May 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com