

# LICA 3



Grease



## Multipurpose Lithium/Calcium grease

### APPLICATION

**Multipurpose grease**  
**General Lubrication**

It is a multipurpose grease, recommended for the lubrication of the bearings and all mechanical parts in the temperature range -30 to 110°C

Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

### SPECIFICATIONS

**International Specification**

ISO 6743-9: L-XCCEA3; DIN 51502: K3H-30

### ADVANTAGES

**Mechanical stability**  
**Thermal stability**

Multipurpose grease  
Miscible with the most other conventional soap greases  
Good mechanical stability  
Good thermal stability

CARACTERISTICS	METHODS	UNITS	LICA 3
NLGI Class	ASTM D 217	-	3
Soap/thickener		-	Lithium / Calcium
Appearance	Visual	-	Smooth
Color	Visual	-	Pale-brown
Dropping point	ASTM D 2265	°C	>170
Penetration at 25°C	ASTM D 217	0.1 mm	220 - 250

Above characteristics are mean values given as information.

**TOTAL Marketing Middle East**  
United Arab Emirates  
Dubai

**LICA 3**  
N° TDS/DXB/16/01/438

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available at [www.quickfds.com](http://www.quickfds.com)