

Section 1. Identification

Product name Viscogen KLK 28
SDS # 450798
Code 450798-FR01

Relevant identified uses of the substance or mixture and uses advised against

Product use Chain lubricant.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier Castrol BP Petco Limited Liability Company
Unit 20.01, level 20, The Nexus , 3A-3B Ton Duc Thang street, Sai Gon ward, Ho Chi Minh City, Vietnam
Tel: 84-28-38219596 / 38219153
Fax: 84-28-38219603 / 38219152
EMERGENCY SPILL INFORMATION: Carechem: +65 3158 1074 (24/7)

Section 2. Hazards identification

Classification of the substance or mixture SKIN SENSITISATION - Category 1
REPRODUCTIVE TOXICITY - Category 2

GHS label elements

Hazard pictograms



Signal word Warning

Hazard statements H317 - May cause an allergic skin reaction.
H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing and eye or face protection.
P261 - Avoid breathing vapour.
P272 - Contaminated work clothing should not be allowed out of the workplace.

Response

P308 + P313 - IF exposed or concerned: Get medical attention.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 - If skin irritation or rash occurs: Get medical attention.
P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage

P405 - Store locked up.

Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 2. Hazards identification

| | |
|--|---|
| Routes of entry | Dermal contact. Eye contact. Inhalation. Ingestion. |
| Other hazards which do not result in classification | Defatting to the skin. |

Section 3. Composition/information on ingredients

| | |
|--------------------------|---------|
| Substance/mixture | Mixture |
|--------------------------|---------|

Synthetic lubricant and additives.

| Ingredient name | CAS number | % |
|---|-------------------|----------|
| N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine | CAS: 68259-36-9 | ≤3 |
| O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate | CAS: 126019-82-7 | <2.5 |
| 1H-Benzotriazole-1-methanamine, N,N-bis (2-ethylhexyl)-ar-methyl- | CAS: 94270-86-7 | ≤0.3 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| | |
|---------------------|--|
| Eye contact | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention. |
| Inhalation | If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention. |
| Skin contact | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. In the event of any complaints or symptoms, avoid further exposure. Get medical attention. If skin irritation or rash occurs: Get medical advice/attention. |
| Ingestion | Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention. |

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

| | |
|-----------------------------------|---|
| Notes to physician | Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | No specific treatment. |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

| | | |
|-------------------------------------|---------------------------------|-------------------------|
| Product name Viscogen KLK 28 | Product code 450798-FR01 | Page: 2/13 |
| Date of issue 02/12/2026. | Format Vietnam | Language ENGLISH |
| Version 9.01 | (Vietnam) | (ENGLISH) |

Section 5. Firefighting measures

Extinguishing media

| | |
|---------------------------------------|--|
| Suitable extinguishing media | In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray. |
| Unsuitable extinguishing media | Do not use water jet. |

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Combustion products may include the following:
phosphorus oxides
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
sulphur oxides (SO, SO₂, etc.)
nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Product name Viscogen KLK 28

Product code 450798-FR01

Page: 4/13

Date of issue 02/12/2026.

Format Vietnam

Language ENGLISH

Version 9.01

(Vietnam)

(ENGLISH)

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m³), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m³). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

| | |
|-----------------|-----------------|
| Physical state | Liquid. |
| Colour | Red. [Light] |
| Odour | Not available. |
| Odour threshold | Not available. |
| pH | Not applicable. |

| | | | | | |
|---------------|-----------------|--------------|-------------|-----------|---------|
| Product name | Viscogen KLK 28 | Product code | 450798-FR01 | Page: | 5/13 |
| Date of issue | 02/12/2026. | Format | Vietnam | Language | ENGLISH |
| Version | 9.01 | (Vietnam) | | (ENGLISH) | |

Section 9. Physical and chemical properties

| | |
|---|-------------------------------------|
| Melting point/freezing point | Not available. |
| Boiling point or initial boiling point and boiling range | Not available. |
| Flash point | Open cup: 280°C (536°F) [Cleveland] |
| Evaporation rate | Not available. |
| Flammability | Not available. |
| Lower and upper explosion limit/flammability limit | Not available. |
| Vapour pressure | |

| Ingredient name | Vapour Pressure at 20 °C | | | Vapour pressure at 50 °C | | |
|---|--------------------------|----------|----------------|--------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | <0.0041 | <0.00055 | ASTM E 1194-87 | | | |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | <0.0041 | <0.00055 | ASTM E 1194-87 | | | |
| Polybutene (Isobutylene/butene copolymer) | 5.10043 | 0.68 | | 13.05111 | 1.7 | |

| | |
|--------------------------------|---|
| Relative vapour density | Not available. |
| Density | <1000 kg/m ³ (<1 g/cm ³) at 15°C |
| Relative density | Not available. |
| Solubility(ies) | |

| Media | Result |
|-------|-------------|
| water | Not soluble |

| | |
|---|-----------------|
| Partition coefficient: n-octanol/water | Not applicable. |
|---|-----------------|

Auto-ignition temperature

| Ingredient name | °C | °F | Method |
|---|------------|----------------|-------------|
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | 343 to 369 | 649.4 to 696.2 | ASTM D 2159 |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | 343 to 369 | 649.4 to 696.2 | ASTM D 2159 |
| Polybutene (Isobutylene/butene copolymer) | 215 | 419 | EU A.15 |

| | |
|----------------------------------|----------------|
| Decomposition temperature | Not available. |
|----------------------------------|----------------|

| | |
|------------------|--|
| Viscosity | Kinematic: 280 mm ² /s (280 cSt) at 40°C Kinematic: 32.7 mm ² /s (32.7 cSt) at 100°C (ASTM D 445) |
|------------------|--|

Particle characteristics

| | |
|-----------------------------|-----------------|
| Median particle size | Not applicable. |
|-----------------------------|-----------------|

Section 10. Stability and reactivity

| | |
|---|---|
| Reactivity | No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information. |
| Chemical stability | The product is stable. |
| Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur. |
| Conditions to avoid | Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | Reactive or incompatible with the following materials: oxidising materials. |
| Hazardous decomposition products | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine

Result

Rat - Oral - LD50

>2000 mg/kg
OECD 423

Rat - Dermal - LD50

>2000 mg/kg
OECD 402

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Rat - Oral - LD50

>2000 mg/kg
OECD 401

Rabbit - Dermal - LD50

>2000 mg/kg
OECD 402

Skin corrosion/irritation

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine

Result

RhE - Skin - Non-irritant to skin.

OECD 439

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Rabbit - Skin - Irritant

OECD 404

Serious eye damage/eye irritation

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine

Result

RhCE - Eyes - Non-irritating to the eyes.

OECD 492

BCOP - Eyes - Non-irritating to the eyes.

OECD 437

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Product name Viscogen KLK 28

Product code 450798-FR01

Page: 7/13

Date of issue 02/12/2026.

Format Vietnam

Language ENGLISH

Version 9.01

(Vietnam)

(ENGLISH)

Section 11. Toxicological information

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutylnaphthalen-1-amine

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Result

Guinea pig - skin

OECD 406

Result: Not sensitising

Guinea pig - skin

OECD 406

Result: Sensitising

Germ cell mutagenicity

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutylnaphthalen-1-amine

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Result

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Cell Gene Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

In vitro - Bacteria

Equivalent to OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Cell Gene Mutation Test]

Result: Negative

Carcinogenicity

Not available.

Reproductive toxicity

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutylnaphthalen-1-amine

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Result

Rat - Oral

OECD 422

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Rat - Oral

OECD 422

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Product name Viscogen KLK 28

Product code 450798-FR01

Page: 8/13

Date of issue 02/12/2026.

Format Vietnam

Language ENGLISH

Version 9.01

(Vietnam)

(ENGLISH)

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

| | |
|---------------------|--|
| Eye contact | No known significant effects or critical hazards. |
| Inhalation | Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. |
| Skin contact | Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction. |
| Ingestion | No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|---------------------|---|
| Eye contact | No specific data. |
| Inhalation | No specific data. |
| Skin contact | Adverse symptoms may include the following: irritation redness dryness cracking reduced foetal weight increase in foetal deaths skeletal malformations |
| Ingestion | Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

| | |
|------------------------------------|----------------|
| Potential immediate effects | Not available. |
| Potential delayed effects | Not available. |

Long term exposure

| | |
|------------------------------------|----------------|
| Potential immediate effects | Not available. |
| Potential delayed effects | Not available. |

Potential chronic health effects

Not available.

Section 11. Toxicological information

| | |
|------------------------------|---|
| General | No known significant effects or critical hazards. |
| Carcinogenicity | No known significant effects or critical hazards. |
| Mutagenicity | No known significant effects or critical hazards. |
| Developmental effects | No known significant effects or critical hazards. |
| Fertility effects | No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name

N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine

Result

Acute - ErC50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EC50

OECD 202

Daphnia

>100 mg/l [48 hours]

Acute - LC50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEC

OECD 201

Algae

100 mg/l [72 hours]

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl-

Acute - ErC50

OECD 201

Algae

0.976 mg/l [72 hours]

Acute - EC50

OECD 202

Daphnia

2.05 mg/l [48 hours]

Acute - LC50

OECD 203

Fish

1.3 mg/l [96 hours]

Chronic - NOEC

OECD 201

Algae

0.32 mg/l [72 hours]

Environmental effects

No known significant effects or critical hazards.

Persistence and degradability

Not expected to be rapidly degradable.

Product/ingredient name

Result

Product name Viscogen KLK 28

Product code 450798-FR01

Page: 10/13

Date of issue 02/12/2026.

Format Vietnam

Language ENGLISH

Version 9.01

(Vietnam)

(ENGLISH)

Section 12. Ecological information

| | |
|--|---|
| N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine | OECD 301B 0% [28 days] - Not readily |
| 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl- | OECD 301B 7% [28 days] - Not readily |

Bioaccumulative potential

Not available.

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|-----|-----------|
| N-phenyl-1,1,3,3-tetramethylbutyl-naphthalen-1-amine | >8 | - | High |
| O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl)phosphorothioate | 20.3 | - | High |

Mobility in soil

Soil/water partition coefficient Not available.

Mobility Liquid. insoluble in water.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | IMDG | IATA |
|-----------------------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. |
| UN proper shipping name | - | - |
| Transport hazard class(es) | - | - |
| Packing group | - | - |
| Environmental hazards | No. | No. |
| Additional information | - | - |

Product name Viscogen KLK 28

Product code 450798-FR01

Page: 11/13

Date of issue 02/12/2026.

Format Vietnam

Language ENGLISH

Version 9.01

(Vietnam)

(ENGLISH)

Section 14. Transport information

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product No known specific national and/or regional regulations applicable to this product (including its ingredients).

International lists

| | |
|--|---|
| Australia inventory (AIC) | At least one component is not listed. |
| Canada inventory | At least one component is not listed in DSL but all such components are listed in NDSL. |
| China inventory (IECSC) | All components are listed or exempted. |
| REACH Status | The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH. |
| Japan inventory (CSCL) | At least one component is not listed. |
| Korea inventory (KECI) | At least one component is not listed. |
| Philippines inventory (PICCS) | All components are listed or exempted. |
| Taiwan Chemical Substances Inventory (TCSI) | All components are listed or exempted. |
| United States inventory (TSCA 8b) | All components are active or exempted. |

Section 16. Other information

History

| | |
|--|--|
| Date of issue/ Date of revision | 12 February 2026 |
| Date of previous issue | 11/11/2025 |
| Prepared by | Product Stewardship |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1 |

📌 Indicates information that has changed from previously issued version.

Notice to reader

| | | |
|-------------------------------------|---------------------------------|-------------------------|
| Product name Viscogen KLK 28 | Product code 450798-FR01 | Page: 12/13 |
| Date of issue 02/12/2026. | Format Vietnam | Language ENGLISH |
| Version 9.01 | (Vietnam) | (ENGLISH) |

Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

| | | |
|-------------------------------------|---------------------------------|-------------------------|
| Product name Viscogen KLK 28 | Product code 450798-FR01 | Page: 13/13 |
| Date of issue 02/12/2026. | Format Vietnam | Language ENGLISH |
| Version 9.01 | (Vietnam) | (ENGLISH) |